DISCOVER THE ADVANTAGES OF THE ZONEMIX SOLUTION















A Multi Zone Audio Mixer A Paging Solution With Scheduling and Control

The ZONEMIX solution provides a 4 or 8 zone mixing and paging solution featuring USB, Ethernet and RS232 connectivity.

Optional wall panel accessories include 3 controller models, a Bluetooth receiver, and a mic/line level input.

The ZMPS paging station can also be included, with each ZONEMIX unit supporting up to 16 stations.

A PC application allows for setup and control of the ZONEMIX and customisation of the wall panels and paging stations.




ZONEMIX CONTROL SOFTWARE








Customise according to your requirements







ZoneMix Features







Key Features







Software designed for complete control

ZONEMIX Control Software - PC Application







Accessories



WP4R

4 Button and Volume Control Knob

 \bullet \bigcirc

WP10

buttons


outputs

10 Button Control

• 10 programmable

• 3 rear contact closure

- 4 programmable buttons
- Volume control knob
- 3 rear contact closure outputs



 \bullet \bigcirc

WPVOL \bullet \bigcirc

S. 10

Volume Control

- Volume control knob
- Level indication and mute



WPBT \bullet \bigcirc

Bluetooth Receiver

- Bluetooth® 5.1 Receiver
- 3.5mm Aux input Bluetooth media controls
- Name, PIN configurable
- Software Setup



WPML \bullet \bigcirc

MIC/Line Input

- Stereo balanced XLR. Mic or Line
- 24V phantom power

• 3.5mm Aux input

- Stereo RCA
- Portrait or landscape




ZMPS

Paging Station

- Programmable buttons for zone and group paging
- Pre-recorded message playback
- Integrated limiter to guarantee voice clarity
- Support for up to 16 paging stations


CUSTOMISE THE LOOK WITH HPM® VIVO™ COVER PLATES






WP4R REAR PANEL

- Euroblock connectors for easy daisy chaining
- Open collector contact closure. 48V, 250mA. Connect outputs to projectors, blinds etc





- ACCESSORY BUS 3
- Zone 1 ZMPS Paging station with no message activation
- Zone 1 WPVOL
 Vol control with level indication
- Zone 3 WP4R Source selection, vol adjustment
- Zone 3 WPBT Bluetooth and local line level source
- Zone 3 ZMPS Paging station with no message activation

ACCESSORY BUS 4

- Zone 4 WP4R Source selection, vol adjustment
- Zone 4 WPML Local bal line level input

Notes

- All accessories including the ZMPS paging station can have a different setup in each zone.
- Only one local audio source from WPBT, WPML etc. can be used on a single Bus



Specifications



	ZONEMIX4	ZONEMIX8	COMMENTS
INPUTS/OUTPUTS			
ZONE OUTPUTS	4	8	
OUTPUT MODE	Stereo/Mono	Mono	
MIC/LINE INPUTS	2		
LINE INPUTS	4		
LOCAL AUDIO INPUTS	4	8	Inputs from Accessory Ports
PAGING STATIONS	Up to 16		
WALL PANELS	Up to 16		
CONTROL			
USER CONTROLS	Front Panel, Wall Panels		
COMMS INTERFACE	USB-C, Ethernet, RS232		PC GUI and 3rd Party API
GENERAL PURPOSE I/O	4 In, 4 Out	8 In, 8 Out	
TONE GENERATOR	5 Tones		Customisable from SD card
SD CARD	WAV: PCM, 16 bit, up to 48kHz sample rate		
AUDIO PERFORMANCE			
FREQUENCY RESPONSE	20Hz - 20kHz		±0.5dB
THD	< 0.01%		20Hz-20kHz, 20kHz BW, Unity Gain
SNR	> 100dBA		Max Output, 1kHz, 20kHz BW, A-Weighted
MECHANICAL			
DIMENSIONS	484 x 160 x 44.5mm (19.0" x 6.3" x 1.7")		W x D x H
WEIGHT	2.4kg	2.4kg	
UNIT HEIGHT	1 RU		
INPUT VOLTAGE	24V DC		100-240Vac 48W plug pack
POWER CONSUMPTION	8W		

Specifications subject to change at any time

ENGINEERED BY AUSTRALIAN MONITOR

Address: Unit 1, 2 Daydream Street, Warriewood NSW 2102 Australia Website: www.australianmonitor.com.au International enquiries email: international@australianmonitor.com.au ABN 86 003 231 187 PROUDLY DISTRIBUTED IN AUSTRALIA AND NEW ZEALAND BY



NEW ZEALAND

AUSTRALIA Phone: 02 9998 7600 Free call: 1800 251 367 sales@ambertech.com.au ambertech.com.au

Phone: +64 (0) 9 443 0753 sales@amber.co.nz **amber.co.nz**